



SPECIFICATIONS:

- SPEED RANGE:** 8 TO 282 RPM
- ROTATION:** CLOCKWISE OR COUNTERCLOCKWISE (FACING THE OUTPUT SHAFT)
- MAXIMUM TORQUE:** 50 In-lbs
- TERMINATION:** OPTIONAL 1/4" SPADE TERMINALS OR 6" WIRE LEADS
- MATERIALS:** PHENOLIC, POWERED IRON AND STEEL
- UL RECOGNIZED, CSA CERTIFIED**
- VOLTAGE:** 12 OR 24 VDC
- BEARINGS:** SELF-ALIGNING OIL IMPREGNATED SINTERED BRONZE
- RoHS COMPLIANT**

NOTES:

- A:** Ø .25 OR Ø .31, LENGTH AND DETAIL TO SUIT OEM REQUIREMENTS
- B:** TERMINATION: OPTIONAL 1/4" SPADE OR 6" WIRE LEAD.
- C:** DIMENSIONS ARE REFERENCE ONLY
- D:** MOUNTING: ALL POSITIONS
- E:** MOUNTING HOLES 4X: .177 Ø THRU, OPTIONAL #10-32 OR M5 X 0.8

OUTLINE DRAWING

| REV | ECN | ND | DATE | BY | CK |
|-----|-----|----|------|----|----|
|-----|-----|----|------|----|----|



3007 29TH Ave East
Bradenton, Florida 34208

| | | | | | |
|--------------------|---------|-----|-----|--|--|
| CUSTOMER NAME & NO | | | | | |
| CATALOG | | | | | |
| 207-SERIES | | | | | |
| DRWN | DATE | CHK | APP | | |
| JTS | 1/20/11 | -- | -- | | |

207-SERIES